




# ANDERSONPOWER™



## Construction & Agriculture Connectivity Solutions



Innovator in Power Connections Since the 1953 Invention of Flat Wiping Technology

Search our offerings for options that include:

- Current Ratings Up to 800 Amps
- 600 Voltage Rating AC/DC
- Flame Resistant Materials
- Sealed Ingress Protection Ratings
- Up to 10,000 Mating Cycles
- Touch Safe Design Features
- Contact Us For Custom Connector Solutions

### New Product Series Spotlight



- Current Ratings Up to 140 Amps
- IP68 Rated
- Up to 8 Signals
- Latching Protection
- Supports CARB Requirements
- Ergonomic Design

[www.andersonpower.com](http://www.andersonpower.com)

# Why Choose Anderson Power For Your Best Connection

## Cycles

•We offer more mating cycles than our competitors

## In-house Testing

•We have in-house UL & TUV labs to get testing done

## Integration

•We are more vertically integrated than the competition

## Global Capabilities

•We have global manufacturing capabilities

	Current Amp Range	Voltage Rating AC/DC	Mating Cycles	Operating Temp.	Housing Style	Power Contacts	Hot Plug	Ground	Touch Safe	Flame Resistance	Mechanically Keyed	Sealed Options	IP Rating
				Chemical Resistant Temp.		Auxiliary Contacts							
<b>SB® Series</b>													
	Up to 500	600	10,000	-20° to 105° C -40° to 105° C	•Wire •Busbar	2 to 3	✓		✓	✓	✓		IP20 IP64 IP10 unmated
<b>SBE® / SBX® Series</b>													
	Up to 550	600	10,000	-20° to 105° C SBX -40° to 105° C SBE	•Wire	2 8	✓		✓	✓	✓		IP20
<b>SBE® Double Stack</b>													
	Up to 700	600	10,000	-40° to 105° C SBE	•Wire	4 16	✓		✓	✓	✓		IP20
<b>SBS® Series</b>													
	Up to 110	600	1,500 to 10,000	-20° to 105° C -40° to 105° C	•PCB •Wire	2 to 3 4	✓	✓	✓	✓	✓		IP20 IP10
<b>SBS® X Series</b>													
	Up to 140	600	5,000	-20° to 105° C	•Wire •Panel Mount	Up to 3 Up to 8	✓	✓	✓	✓	✓	✓	IP68
<b>SPEC Pak®</b>													
	Up to 80	600	1,500	-40° to 105° C	•Wire	Up to 5 Up to 8	✓		✓	✓	✓	✓	IP68
<b>DIN E Series - Euro Battery Connector</b>													
	Up to 400	600	5,000	-25° to 75° C	•Wire	2 4	✓		✓	✓	✓		IP23
<b>DIN A Series - Battery Connector</b>													
	Up to 450	600	5,000	-25° to 75° C	•Wire	2 4			✓	✓	✓		IP23
<b>DIN Double Stack</b>													
	(E) Up to 800 (A) Up to 650	600	5,000	-25° to 75° C	•Wire	4 8			✓	✓	✓		IP23



Anderson Power Products  
13 Pratts Junction Road  
Sterling, MA 01564  
978.422.3800  
www.andersonpower.com



Pactech  
2260 Trade Zone Blvd.  
San Jose, CA 95131  
408.526.9363  
sales@pactech-inc.com  
www.pactech-inc.com

All Data Subject to Change Without Notice

©2023 Anderson Power Products Inc., all rights reserved. Anderson Power Products®, SB®, SBS®, SBE®, SPEC Pak® SBX® and the Anderson Power Logo are registered trademarks of Anderson Power Products, Inc.